



RH1215KDPB

21.5" WIDESCREEN MONITOR



★ FEATURES

- 21.5" TFT Full HD Panel, 1920(H) x 1080(V)
- Flat panel design, with optional P-Cap Touch (10 points)
- Strong Aluminum Frame with slot-less metal back cover
- Support USB (Type C) or HDMI (Type A), VGA input
- Support 75mm x 75mm or 100mm x 100mm standard base



RH1215KDPB

21.5" WIDESCREEN MONITOR

SPECIFICATIONS

PANEL	Active Area (mm)	476.064 (H) x 267.786 (V)
	Resolution	1920(H) x 1080(V)
	Display Colors	262K, 6 bits Color Depth
	Brightness/Contrast	250 cd/m ² / 3000:1
SIGNAL INPUT	LED Life Time	30,000 hours (IF = 20mA)
	USB (Type C)	USB 2.0 for DP156A-U
	HDMI (Type A)	Digital for DP156A-H
POWER ADAPTOR	VGA	Analog for DP156A-V
	Input	Universal AC 100~240V, 50/60Hz
	Output	DC 12V 2A
POWER	Management	VESA DPMS
	Consumption	<= 4W
TOUCH	P-CAP	Support 10 multiple touch points
MOUNTING	Standard	75mm x 75mm or 100mm x 100mm, M4
ENVIRONMENT	Operating Temperature	0 C° to +50 C°
	Storage Temperature	-20 C° to +60 C°
	Operating Humidity	10% to 85%